

# MIP3P / MIP3T / MIP3F

**Rugged. Reliable. Wireless.**



MIP3P



MIP3T



MIP3F

The MIP3P, MIP3T and MIP3F Vehicle Printers with the latest technology interfaces are designed to maximize efficiency in route accounting applications as well as ticket & report printing.

Available in either Tractor or Friction feed; a Portable model with an integrated paper tray, battery and charging system are included in the portable version.

#### **Key Features**

- Wireless printing
- Trouble-free installation
- Easy paper loading
- Easy-to-use control panel
- Simple to change ribbon

#### **Ideal Applications**

- Route Accounting Applications (DSD): Invoice & Report Printing
- Public Safety Applications: Ticket & Report Printing

#### **Interfaces:**

- Serial/Parallel
- Bluetooth/Serial
- 802.11b/Serial

Consumables

Ink Jet Printers

Laser Printers

Line Matrix Printers

**Serial Matrix Printers**

# MIP3P / MIP3T / MIP3F

Vehicle Printers

## Features & Specifications

<b>Printing Technology</b>	Serial Impact Dot Matrix, bi-directional or uni-directional
<b>Print Head</b>	9-wire
<b>Print Speed</b>	288 cps Draft Elite
<b>Character Sets</b>	Full ASCII character set graphics and international character sets supported special printing capabilities: NLQ, Bold, Italics, Underline, Subscript, Superscript, Draft and compressed, mugshot capability
<b>Paper</b>	Multiple copies, 3-sheet plus original
<b>Consumables</b>	Long life black ribbon cartridge
<b>Emulations</b>	IBM® ProPrinter III
<b>Interfaces</b>	Serial, Parallel, USB, 802.11b, Bluetooth
<b>Physical Specifications (HxWxD)</b>	MIP3P: 305 x 381 x 110 mm - Weight = 4.5 Kg MIP3T: 142 x 381 x 110 mm - Weight = 2.4 Kg MIP3F: 142 x 381 x 110 mm - Weight = 2.4 Kg
<b>Operating Environment</b>	Power: 12 to 24 volts DC Max Vehicle Power DC 5A Power Supply (optional); Built-in power conditioning to protect against power surges and spikes  Temperature: Operating: 14° to 122°F (-10° to 50°C); Storage: -4° to 158° F (-20° to 70° C)  Humidity: 15% to 95% relative (non-condensing)



Rutherford Road, Basingtoke,  
Hampshire, RG24 8PD

Tel: +44 (0)1256 481481  
[www.tallygenicom.co.uk](http://www.tallygenicom.co.uk)