

T2024/24



The quality 24 pin entry level business Dot Matrix printer.

The T2024-24 is a surprisingly robust little printer, considering it's amongst the least expensive of the 24 pin machines available today. With low running costs, high quality output and a small footprint it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels used in the warehouse or factory.

An optional sheet feeder for printing batches of cut forms widens the possibilities.

An easy-to-use control panel is supplemented by a suite of disk based utilities to customize all printer set up functions. Automatic top of form, automatic paper loading and Zero tear with no wasted forms makes the printer very easy to use, and with minimal training required.

Mono Laser
Colour Laser
Production Ink
Dot Matrix
Line Matrix
Consumables

- High quality 24 pin print head.
- Parallel and RS232 Serial interfaces as standard.
- IBM ProPrinter and Epson FX emulation's for easy connection on a wide variety of hosts.
- Automatic top of form for easy alignment.
- Rear feed with paper park facility for easy switching between forms.
- Zero tear off for now wasted forms.
- Automatic paper loading.
- Automatic sheet feeder option.

T2024/24

Features & Specifications

Dot Matrix Printer

Printing technology	Serial impact dot matrix		
Printer types	Mono, 80 columns, 24-pin		
Workload	8,000 pages per month		
Advanced Automatic features	Paper loading, paper parking, top of form and zero tear off.		
Print speed - std		Draft	LQ
Characters per second	10 cpi	200	66
	12 cpi	240	80
	15 cpi	300	100
Throughput (ECMA 132)		Letter Performance	Spreadsheet
	T2024/24	254 (at 10 cpi)	130 (at 17 cpi)
Character pitch	10, 12, 15, 17.1, 20 cpi		
Graphics resolution	Up to 360 x 360 dpi		
Line pitch	6, 8lpi		
Fonts	3 x draft, pica, elite, micron, 7 x LQ, Courier, Bold PS, prestige, script, san serif, roman, OCR-B, 6 x scalable, courier, bold PS, prestige, script, san serif, roman		
Paper handling - std	Tractor paper - rear push tractors with paper parking Cut sheet - single sheet insertion (top)		
Paper handling - opt	Single bin automatic sheet feeder (80 sheets)		
Paper types	Tractor paper 115 to 254mm max width Cut sheet 102 to 297mm max width Cut sheet 127 to 363mm max length		
Multi-part stationery	1+4 copies		
Interfaces - std	Serial RS232 and Parallel (Bi-directional) with automatic switching between ports. 54Kb buffer selectable in steps 0, 8, 22, 54Kb		
Emulations - std	IBM ProPrinter XL24E, Epson LQ300 (ESC 2P) not colour		
Host Support includes	Windows operating environments, UNIX, SAP-R3, DOS, VMS and legacy systems		
Noise level (ISO 7779)	55dB(A)		
Power supply	230V 110/120V version available		
Print head life	200 million characters		
Consumables	Ribbon: 6 million characters		
Weight	5.2Kg		
Dimensions	(HxWxD): 140 x 434 x 326mm		
Reliability	MTBF: 10,000 hours		

NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.



Rutherford Road, Basingstoke,
Hampshire, RG24 8PD.
Tel: UK 0800 652 4557
International: +44 (0) 1256 481 521
Fax: UK 0870 872 2889
Web: www.tallygenicom.co.uk