

# T9220/T9220N

## Setting new standards for price and performance



The T9220 superior performance monochrome laser printer is designed for business applications and demanding network environments. When comparing print quality, print speed, paper handling and functionality, the T9220 is the price/performance leader.

The engine speed of 20 pages per minute combined with 16MB of RAM and a high-speed processor deliver exceptional throughput with less than 12 seconds to print first page. With 1200 DPI resolution, TallyGenicom's T9220 laser printer produces crisp text and eye-catching graphics that make the right impression.

### **Mono Laser**

Colour Laser

Production Ink

Dot Matrix

Line Matrix

Consumables

- Superior performance at 20 pages per minute
- Robust monthly workload up to 100,000 pages
- Standard Ethernet 10/100 Base-T connectivity (N version)
- Tally Network Printer Manager allows easy set up, configuration and administration
- Impressive paper handling with an input capacity of up to 1100 sheets
- Double sided printing as standard
- Auto Run CD provides easy installation and set up
- Excellent cost of operation

# T9220/T9220N

## Features & Specifications

### Mono Laser Printer

<b>Printing Technology</b>	Laser
<b>Processor</b>	166 Mhz 32 Bit RISC
<b>Print Speed - Mono</b>	Up to 20 pages per minute
<b>Monthly Workload - Average</b>	8,000 pages
<b>Max</b>	100,000 pages ( one time peak use )
<b>Print Resolution - Max</b>	1200 dpi
<b>Memory - Standard</b>	16 Mb
<b>Memory - Max</b>	80 Mb
<b>Emulation - Standard</b>	PCL6, PCL5e, Epson, IBM Proprinter
<b>Emulation - Optional</b>	PostScript Level 3 PDL, Barcode (T9220 only)
<b>Fonts</b>	1 Bit Map and 45 scaleable, 135 PS3 fonts, 39 barcodes OCR B and PDL (T9220N only)
<b>Paper handling input - Standard</b>	Manual feed, 100 sheet multi-purpose feeder (MPF) + 500 sheet universal cassette
<b>Duplex printing</b>	Standard
<b>Paper handling input - Optional</b>	2nd universal cassette accepts 500 sheets
<b>Paper handling output - Standard</b>	250 sheet face down
<b>Print media type</b>	MPF - paper, transparencies, labels, heavy paper stock, envelopes Standrad cassette - paper Optional cassette - paper
<b>Paper sizes</b>	MPF - A4, Letter, Legal, Folio, A5 Executive, Statement, ISO B5, JIS B5, A5, A6 Std cassette - A4, Letter, Legal, Folio, Executive, ISO B5, JIS B5 and Yes A5 Optional cassette - A4, Letter, Legal, Folio Executive, ISO B5, JIS B5, A5 Duplex - A4, Letter, Legal, Folio
<b>Envelope sizes( MPF )</b>	COM 10, Monarch, C5, C6, DL
<b>Non-printable area</b>	4mm from each edge / envelopes - 15mm from left and 10mm from all other sides
<b>Media weight</b>	Cassette - 60-105gsm MPF - 60 - 163gsm
<b>Printer drivers</b>	Windows 9.x/NT 4.0/2000/ XP/MAC/ME, Linux and Unix Posters, N-Up, Booklets, Duplex, Forms, Overlays, Watermarks.
<b>Interfaces - Standard</b>	Parallel (Bi-directional IEEE 1284 compliant ECP/Nibble/Byte Mode), USB (v 2.0)
<b>Interfaces - Optional</b>	Serial RS232, Internal Ethernet (10BaseT & 100BaseTx), Wireless Lan (802.11b)
<b>Interface intelligence</b>	Automatic Interface Switching
<b>First page print time</b>	11secs or less
<b>Warm-up time</b>	Less than 50 secs
<b>Acoustic level (ISO 7779)</b>	Printing -52dBA Standby - 35dBA Sleep Mode - Background level
<b>Power consumption</b>	Energy Star Compliant, Average: 350W Standby: 100W Sleep Mode: 20W
<b>Weight</b>	13.5Kg (with consumables)
<b>Dimensions</b>	386(w) x 436(d) x 326(h) mm
<b>Input Voltage</b>	220 - 240V 50/60Hz
<b>Operating Environment - Temperature</b>	10°C - 32°C
<b>Operating Environment - Humidity</b>	20% - 80% relative humidity, non condensing
<b>MTBF</b>	60,000 pages ( Power on 8hr/day in recommended duty cycle )
<b>MTTR</b>	30 minutes
<b>Consumables</b>	Replacement process unit - 8,000 pages* ( *Based on 5% coverage of A4 page )
<b>Options</b>	2nd cassette (500 sheet), PostScript Level 3 PDL & Barcode SIMM (T9220 only), 16/32/64Mb Memory, Serial Interface, Internal Ethernet 10BaseT & 100BaseTx (T9220 only), Barcode SIMM, Process Unit, Wireless LAN

**NB: Paper is a highly variable medium, and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.**



Rutherford Road, Basingstoke,  
Hampshire, RG24 8PD.  
Tel: UK 0800 652 4557  
International: +44 (0) 1256 481 521  
Fax: UK 0870 872 2889  
Web: [www.tallygenicom.co.uk](http://www.tallygenicom.co.uk)